

Husqvarna® Bar & Chain Applications

Bars

1	BAR DESCRIPTION	2	MOUNT	3	PITCH	4	GAUGE	5	DRIVE LINK
---	-----------------	---	-------	---	-------	---	-------	---	------------

1 DESCRIPTION

- HL = Laminated, Sprocket Nose Guide Bar
- HLN = Laminated, Narrow Sprocket Nose Bar (Pixel or Micro-Lite)
- FT = FARM Tough - Bar for Rancher models, 359 or 460, Laminated
- HT = Oregon - Power Match, Replaceable Tip, Sprocket Nose Guide Bar
- HTR = Oregon - Power Match, Replaceable Tip, Reduced Weight, Sprocket Nose Guide Bar
- HA = Oregon - Armor Tip, Solid Nose Guide Bar
- EMAB = Electrolux Motors AB - Professional Quality Laminated Bars, Sprocket Nose Bar

2 MOUNT

- 1 = SMALL MOUNT - AO41
136, 137, 141, 142, 235 and 240
- 2 = SMALL MOUNT - K095
55 Rancher, 242XP, 254XP, 257, 261, 262XP, 334T, 335XPT, 336, 338XPT, 339XP, 340, 345, 350, 353
346XP, 362XP, 357XP, 359, 435, 440, 445, 450, 455 Rancher, 460, 460 Rancher
- 3 = LARGE MOUNT - D009
61, 266XP, 268, 272XP, 365, 371XP, 372XP, 281XP, 288XP, 385XP, 390XP, 394XP, 395XP, 3120XP, 570, 575XP, 576XP

NOTE:

Compact 23 takes an Oregon A041 mount. Models 36 & 41 can also use this mount.

3 PITCH

- 5 = .325"
- 8 = 3/8"
- 4 = .404"

4 GAUGE

- 0 = .050"
- 8 = .058"
- 3 = .063"
- 6 = .043"

Bar Reference I.D.

HT	3	8	0-	72
1	2	3	4	5

5 DRIVE LINK COUNT

Number of Drive Links in the Chain Loop

1	BAR DESCRIPTION	2	MOUNT	3	PITCH	4	GAUGE	5	DRIVE LINK
---	-----------------	---	-------	---	-------	---	-------	---	------------

Example: HL258-66

Husqvarna Branded, Oregon Laminated Bar, Small Husqvarna Mount, 325" Pitch, .058" Gauge, 66 Drive Links

Example: HT380-72

Husqvarna Branded, Oregon Power Match Bar, Large Husqvarna Mount, 3/8" Pitch, .050" Gauge, 72 Drive Links

Chain

Models 36, 136, 40, 41, 141, 42, 45, 51 and 55, 235, 240 are recommended with Low Kickback Chain (Blue Label) to comply with ANSI B 175.1-2000 Standards. Professional Chains (Yellow Label) will pass the Standards, but should only be supplied upon the customer's specific request. A signed receipt stating the request is suggested.

Models 42, 246, 242XP, 257, 351, 353, 357XP, 359, and 346XP, 435, 440, 445, 450 are Recommended with either Low Kickback (Blue Label) or Professional Chain (Yellow Label) depending on the User's Preference. A signed receipt is again suggested for the Professional Chains.

Models 61 and 55 Rancher Must be set up with Low Kickback Chain (Blue Label) H80/H81 (72/73V) to Meet ANSI Standards.

Models above 3.8 cubic inches are recommended with Professional Chain (Yellow Label). Includes 261, 262XP, 266XP, 268, 272XP, 362XP, 365, 371XP, 372XP, 575XP, 576XP, 281XP, 288XP, 385XP, 390XP, 394XP, 395XP, and 3120XP.

HUSQVARNA® BAR & CHAIN FIT UP CHART



**The suggested bar & chain types are based on the most common Original Equipment Combinations

	Chainsaw Model	Bar Length	Bar Type	Chain Type	Drive Links	Chain Pitch	Chain Gauge
LAMINATED BARS WITH SPROCKET TIPS	335XPT (Intenz)	12"	HLI-280-45	H36-45	45	3/8"	.050"
		14"	HLI-280-52	H36-52	52	3/8"	.050"
		16"	HLI-280-56	H36-56	56	3/8"	.050"
	316E, 334T, 335XPT, 338XPT, 323P4, 325P4, 326P5x	10"	HL-280-40	H36-40	40	3/8"	.050"
		12"	HL-280-45	H36-45	45	3/8"	.050"
		14"	HL-280-52	H36-52	52	3/8"	.050"
	339XP	16"	HLN250-66	H30-66	66	.325"	.050"
		136, 137, 141, 142	16"	HL-180-56	H36-56	56	3/8"
				*164MLEA041	90SG-56	56	3/8"
	235, 240	14"	HL180-52	H36-52	52	3/8"	.050"
		16"	HL180-56	H36-56	56	3/8"	.050"
	50, 51, 55, 336, 340, 345, 350, 346XP, 351, 353, 435, 440, 445, 450	13"	HLN-250-56	H30-56	56	.325"	.050"
		16"	HLN-250-66	H30-66	66	.325"	.050"
		18"	HLN-250-72	H30-72	72	.325"	.050"
		20"	HLN-250-80	H30-80	80	.325"	.050"
	36, 41, 50, 51, 55, 336, 340, 345, 350, 346XP, 351, 353, 435, 440, 445, 450	16"	HL-258-66	H38-66	66	.325"	.058"
		18"	HL-258-72	H38-72	72	.325"	.058"
		20"	HL-258-78	H38-78	78	.325"	.058"
55 Rancher, 359, 455 Rancher, 460, 460 Rancher	18"	FT-280-68	H80-68	68	3/8"	.050"	
	20"	FT-280-72	H80-72	72	3/8"	.050"	
	18"	FT-288-68	H81-68	68	3/8"	.058"	
	20"	FT-288-72	H81-72	72	3/8"	.058"	
SOLID BARS WITH REPLACEABLE SPROCKET TIPS	51, 55, 336, 340, 345, 350, 346XP, 351, 353, 440, 445, 450	20"	HT-250-78	H37-78	78	.325"	.050"
		16"	HT-258-66	H38-66	66	.325"	.058"
		18"	HT-258-72	H38-72	72	.325"	.058"
		20"	HT-258-78	H38-78	78	.325"	.058"
	257, 261, 262, 262XP, 357, 359, 455 Rancher, 460, 460 Rancher	16"	HT-280-60	H46-60	60	3/8"	.050"
		18"	HT-280-68	H46-68	68	3/8"	.050"
		20"	HT-280-72	H46-72	72	3/8"	.050"
		16"	HT-288-60	H48-60	60	3/8"	.058"
	61, 66, 266, 365, 288XP, 372XP, 385XP, 390XP, 394XP, 395XP, 3120XP, 570, 575XP, 576XP	18"	HT-288-68	H48-68	68	3/8"	.058"
		20"	HT-288-72	H48-72	72	3/8"	.058"
		16"	HT-380-60	H46-60	60	3/8"	.050"
		18"	HT-380-68	H46-68	68	3/8"	.050"
		20"	HT-380-72	H46-72	72	3/8"	.050"
		24"	HT-380-84	H46-84	84	3/8"	.050"
		28"	HT-380-93	H46-93	93	3/8"	.050"
		16"	HT-388-60	H48-60	60	3/8"	.058"
		18"	HT-388-68	H48-68	68	3/8"	.058"
		20"	HT-388-72	H48-72	72	3/8"	.058"
		24"	HT-388-84	H48-84	84	3/8"	.058"
		28"	HT-388-93	H48-93	93	3/8"	.058"
	3120XP	32"	HT-343-95	H57-95	95	.404"	.063"
		36"	HT-343-104	H57-104	104	.404"	.063"
SOLID BARS WITH ARMOR TIP	55 Rancher, 257, 261, 362XP, 357XP, 576XP, 359, 455 Rancher, 460, 460 Rancher	16"	HA-280-60	H46-60	60	3/8"	.050"
		18"	HA-280-68	H46-68	68	3/8"	.050"
		20"	HA-280-72	H46-72	72	3/8"	.050"
	365, 288XP, 372XP, 385XP, 390XP, 394XP, 395XP, 570, 575XP, 576XP	16"	HA-380-60	H46-60	60	3/8"	.050"
		18"	HA-380-68	H46-68	68	3/8"	.050"
		20"	HA-380-72	H46-72	72	3/8"	.050"
		24"	HA-380-84	H46-84	84	3/8"	.050"

*Fits models 137 & 142 AFTER Serial Number 2006100001

